

Specification

Image

Native Resolution	: 800 x 600
Maximum Resolution	: 1920 x 1200
Standard Mode Brightness	: 4000 lm
Native Aspect Ratio	: 4:3
Compatible Aspect Ratio	: 16:9
Contrast Ratio	: 20,000:1
Throw Ratio	: 1.94 to 2.16 (1295.40 mm@2000 mm)
Digital Zoom	: 2x
Vertical Keystone Correction	: -40°/+40°
Maximum Vertical Sync	: 120 Hz
Maximum Horizontal Sync	: 100 kHz
Minimum Vertical Sync	: 24 Hz
Minimum Horizontal Sync	: 15 kHz
Color Supported	: 1.07 Billion Colors (30-bit)

Projection Lens

Minimum Lens Aperture	: F/2.41
Maximum Lens Aperture	: F/2.53
Minimum Focal Length	: 21.85 mm
Maximum Focal Length	: 24.01 mm
Minimum Diagonal Image Size	: 584.20 mm
Maximum Diagonal Image Size	: 7.62 m (300")
Minimum Projection Distance	: 1 m
Maximum Projection Distance	: 11.80 m
Optical Zoom	: 1.1x

Lamp

Lamp Type	: OSRAM
Number of Lamps	: 1
Lamp Power	: 220 W
Normal Mode Lamp Life	: 6000 Hour
Economy Mode Lamp Life	: 7000 Hour
Extreme Eco Mode Lamp Life	: 10000 Hour

Interfaces/Ports

HDMI	: Yes
Number of USB Ports	: 1
USB	: Yes
USB Connector Type	: 1 x Type-A
Composite Video	: Yes
Number of VGA Inputs	: 1
VGA In	: Yes
Number of VGA Outputs	: 1
VGA Out	: Yes
Number of Audio Inputs	: 1
Number of Audio Outputs	: 1
Audio Line In	: Yes
Audio Line Out	: Yes
Total Number of HDMI Ports	: 1

Technical Information

Projection System : DLP

Projection Method

Ceiling

Front

Rear

Rear Ceiling

Video Compatibility

EDTV

HDTV

NTSC

PAL

SDTV

SECAM

Computer Compatibility

Mac PC

Windows PC

Audio

Number of Speakers : 1
Speaker Output Power : 3 W
Speaker Output Mode : Mono

Power Description

Power Supply : 100 V AC ~ 240 V AC
Input Voltage : 120 V AC
: 230 V AC
Operating Power Consumption : 275 W

Physical Characteristics

Fan Noise : 24 dB Approximate Economy Mode
: 32 dB Approximate Standard Mode
Temperature : 0°C to 40°C
Humidity : 80% Maximum Relative Humidity
Weight (Approximate) : 2.80 kg
Form Factor : Ceiling Mountable
Height : 113.7 mm
Width : 313 mm
Depth : 240 mm

Miscellaneous

Package Contents

X1126AH DLP Projector
AC Power Cord
VGA Cable
Remote Control
Battery for Remote Control
Lens Cap
Quick Start Guide
Security Card

Optional Accessories

3D Glasses
Dust Filter

Warranty

3 Years Warranty
(01 Year for Lamp)